



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/574,023	01/17/2007	Zvi Reznic	P-9912-US	9777

56639 7590 03/03/2011
EITAN MEHULAL LAW GROUP
10 Abba Eban Blvd. PO Box 2081
Herzlia, 46120
ISRAEL

EXAMINER

KIM, HEE-YONG

ART UNIT	PAPER NUMBER
----------	--------------

2482

NOTIFICATION DATE	DELIVERY MODE
-------------------	---------------

03/03/2011

ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

PUSDKT@EM-LG.COM

Office Action Summary	Application No. 10/574,023	Applicant(s) REZNIC ET AL.	
	Examiner HEE-YONG KIM	Art Unit 2482	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 31 December 2010.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 12-54 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 12-54 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(c)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Amendment

1. This office action is in reply to Applicant's Response dated December 31, 2010.
2. **Claims 55-63** have been cancelled.
3. **Claims 12, 26, 42, and 50** have been amended.
4. **Claims 12-54** are pending.

Response to Arguments

5. Objection to **claim 57** is withdrawn because of cancellation of claims.
6. Applicant's arguments with respect to the prior art rejection over **claims 12-54** have been considered but they are not persuasive.
7. Applicant argues (pp.13-14) that MPEG standard used in Schreiber does not teach the claim limitation "the difference between an image and its own value coarse value representation", because the delta information of the MPEG standard is based on a comparison of an image frame to be transmitted and either (1) a prior or (2) a future image frame of video. Examiner respectfully disagrees and would like to point out that the reference (Schreiber) has to be read as a whole. Fig.6 in Schreiber clearly shows that MPEG video compression is performed in the coarse level, but the coarse signal is reconstructed by adding the prediction and the residual (delta in applicant's notation), and then it is subtracted from the original signal to give a rise to the next level (refinement level). Applicant further argues (pp.14-15) that the new limitation introduced in the amendment - "spatial proximity between two symbols, each of which two symbols

Art Unit: 2482

is associated with a different respective refinement value is related to a numeric proximity between the respective refinement values”, is distinct from any known art. Examiner respectfully disagrees. Schreiber discloses that in Fig.7 spatial approximation is represented by the distance between 64 PSK digital constellation and the analog signal (radial distance from it), and the analog signal is related to the representation of the refinement signal.

Claim Rejections - 35 USC § 102

8. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

9. **Claims 26, 28-29, 33-34, 36, 37, and 39-40** are rejected under 35 U.S.C. 102(b) as being anticipated by Schreiber (Proceedings of the IEEE, vol.83, No.6).

Regarding **claim 26**, Schreiber discloses Advanced Television Systems for Terrestrial Broadcasting: Some Problems and Some Proposed Solutions. Schreiber specifically discloses A method of transmitting video images, comprising:
providing a video image (Video In, Fig.1);
compressing the video image into a coarse portion (coder 1, Fig.1);
representing a difference (subtracted from original video, Fig.1) between the coarse portion and the video image by a refinement portion (output of coder 2, Fig.1) in value form (examiner maintains that the difference is a numerical value such as pixel difference);

Art Unit: 2482

mapping the coarse portion and at least part of the refinement portion into symbols of a constellation (Fig.7 Constellation), such that spatial proximity between two symbols, each of which two symbols is associated with a different respective refinement value (Fig.7 shows the hybrid constellation - 64 PSK digital signal (coarse symbol) which should be dots in the constellation with 64 angular directions without line segments, and the analog signal is represented by the length of lines at each digital signal constellation), is related to a numeric proximity (Refinement portion is representation of the residual - subtraction of coarse signal from the original signal as shown in Fig.1) between the respective refinement values; wherein the refinement portion is mapped uncompressed (higher levels of the coder generates analog signal, pp.974, second col, last line); and transmitting the mapped symbols to a receiver (Transmitter at Fig.8).

Regarding **claim 28**, Schreiber discloses everything claimed above (see claim 26). Schreiber further discloses wherein mapping the portions comprises mapping the coarse and refinement portions separately into symbols and superimposing the symbols onto each other (Schreiber: Fig.7 Hybrid Constellation).

Regarding **claim 29**, Schreiber discloses everything claimed above (see claim 28). Schreiber further discloses wherein mapping the portions comprises mapping the refinement portion into symbols of a constellation having a side to side distance smaller than the distance between the symbols of a constellation of the symbols of the coarse portion (Schreiber: Fig.7). Examiner interprets the side to side distance as angular distance between the digital signals. Therefore the refinement portion (analog signal in

Art Unit: 2482

Schreiber) does not have this component (zero distance), but has a perpendicular component.

Regarding **claim 33**, Schreiber discloses everything claimed above (see claim 26). Schreiber further discloses wherein representing the difference by a refinement portion comprises determining for each pixel a difference between the coarse portion and the provided image and wherein each value of the refinement portion represents a difference (subtracted from original video, Fig.1) between the coarse portion and the provided image at a point on the image.

Regarding **claim 34**, Schreiber discloses everything claimed above (see claim 33). Schreiber further discloses wherein each value of the refinement portion represents a difference between the coarse portion and the provided image at a point on the image coinciding with a pixel (subtracted from original video, Fig.1, it was anticipated that subtraction is done by pixel by pixel).

Regarding **claim 36**, Schreiber discloses everything claimed above (see claim 26). Schreiber further discloses wherein mapping the portions comprises mapping the refinement portion into symbols of a constellation having a bin (angular distance between neighboring constellations in Fig.7) for each of the possible values of the difference between the coarse portion and the provided image for a specific point on the image.

Regarding **claim 37**, Schreiber discloses everything claimed above (see claim 26). Schreiber further discloses wherein the refinement portion is mapped uncoded (Analog, Schreiber: Level 2 Analog, Fig.8) into symbols. Examiner maintains that the

Art Unit: 2482

refinement portion can be transmitted either by Level 2 digital only or by Level 2 Analog only in Schreiber (Fig.8) without level 3.

Regarding **claim 39**, Schreiber discloses everything claimed above (see claim 26). Schreiber further discloses wherein the coarse portion is protected by a forward error correction code Schreiber: FEC, Fig.8), while the refinement portion (Schreiber: Level 2 Analog, Fig.8) is transmitted without protection by a forward error correction code.

Regarding **claim 40**, Schreiber discloses everything claimed above (see claim 26). Schreiber further discloses wherein mapping the portions comprises mapping the refinement portion into a constellation having a discrete number of possible values (digital, Level 2 Digital, Fig.8). Examiner maintains that the refinement portion can be transmitted either by Level 2 digital only or by Level 2 Analog only in Schreiber (Fig.8) without level 3.

Claim Rejections - 35 USC § 103

10. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

11. **Claims 12-22, 24-25, 27, 31-32, 35, and 38** are rejected under 35 U.S.C. 103(a) as being unpatentable over Schreiber in view of Seroussi (US 5,764,374), hereafter referenced as Seroussi.

Regarding **claim 12**, Specifically Schreiber discloses A method of transmitting video images (Fig.1), comprising:

- providing a video image (Video In, Fig.1);
- compressing the video image into a coarse portion (coder 1, Fig.1), which has, for at least one color component (Well known in the art that video is compressed in 3 color components, RGB or YUV);
- representing the difference (subtracted from original video, Fig.1) between the coarse portion and the video image by a refinement portion (output of coder 2, Fig.1) in value form;
- mapping the coarse portion and at least part of the refinement portion into symbols of a constellation (Fig.7 Constellation), such that spatial proximity between two symbols, each of which two symbols is associated with a different respective refinement value (Fig.7 shows the hybrid constellation - 64 PSK digital signal (coarse symbol) which should be dots in the constellation with 64 angular directions without line segments, and the analog signal is represented by the length of lines at each digital signal constellation), is related to a numeric proximity (Refinement portion is representation of the residual - subtraction of coarse signal from the original signal as shown in Fig.1) between the respective refinement values; and
- transmitting the mapped symbols to a receiver (Transmitter at Fig.8).

However Schreiber fails to disclose a bounded difference from the provided image, for a predetermined set of the pixels of the image.

In the analogous field of endeavor, Seroussi discloses System and Method for Lossless Image Compression Having Improved Sequential Determination of Golomb Parameter. Seroussi specifically discloses near –lossless compression based on a bounded difference from the provided image (Uniform bound E (e.g. 1, 2, 5, 7) on the difference between each original pixel and its decoded pixel, col.25, line 40-43), for a predetermined set (all the pixels) of the pixels of the image, in order to provide low complexity compression (col.6, line 54-56).

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber by substituting the source coding based on MPEG (Fig.6) for the level 1 (coarse portion) with near-lossless encoder, in order to provide low complexity compression. The Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near – lossless compression based on a bounded difference from the provided image, has all the features of claim 12.

Regarding **claim 13**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near –lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein compressing the video image comprises compressing such that the difference between the coarse portion and the provided image is bounded for substantially all the pixels of the image (all the pixels in image).

Regarding **claim 14**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near –lossless compression based on a

Art Unit: 2482

bounded difference from the provided image, as applied to claim 12, discloses wherein compressing the video image comprises compressing such that the difference between the coarse portion and the provided image is bounded to have at most ten different possible values (Seroussi: Uniform error bound 4 (col.25, line 40-43), means 0, +/-1, +/-2, +/-3, +/-4, which has 9 different possible values).

Regarding **claim 15**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein compressing the video image comprises compressing such that the difference between the coarse portion and the provided image is bounded to have at most five different possible values (Seroussi: Uniform error bound 2 (col.25, line 40-43), means 0, +/-1, +/-2, which has 5 different possible values).

Regarding **claim 16**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein the difference between the coarse portion and the provided image is bounded by a maximal value which is less than 5% of the possible values of the provided images, because the pixel is usually represented by 8 bits and therefore there are 256 possible values and 5% of 256 is about 13. Seroussi already discloses uniform bound 1, 2, 5, and 7 which are less than 5% of possible values.

Regarding **claim 17**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a

Art Unit: 2482

bounded difference from the provided image, as applied to claim 12, discloses wherein compressing the video image comprises compressing such that the difference between the coarse portion and the provided image is bounded for substantially all the color components representing the image (Seroussi: color space (RGB or YUV), col.1, line 56).

Regarding **claim 18**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein mapping the portions comprises mapping the coarse and refinement portions separately into symbols and superimposing the symbols onto each other (Schreiber: Fig.7 Hybrid Constellation).

Regarding **claim 19**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a bounded difference from the provided image, as applied to claim 18, discloses wherein mapping the portions comprises mapping the refinement portion into symbols of a constellation having a side to side distance smaller than the distance between the symbols of a constellation of the symbols of the coarse portion (Schreiber: Fig.7). Examiner interprets the side to side distance as angular distance between the digital signals. Therefore the refinement portion (analog signal in Schreiber) does not have this component (zero distance), but has a perpendicular component.

Regarding **claim 20**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a

Art Unit: 2482

bounded difference from the provided image, as applied to claim 12, discloses wherein the coarse portion is protected by a forward error correction code (Schreiber: FEC, Fig.8), while the refinement portion (Schreiber: Level 2 Analog, Fig.8) is transmitted without protection by a forward error correction code.

Regarding **claim 21**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein the refinement portion is mapped uncoded (Analog, Schreiber: Level 2 Analog, Fig.8) into symbols. Examiner maintains that the refinement portion can be transmitted either by Level 2 digital only or by Level 2 Analog only in Schreiber (Fig.8) without level 3.

Regarding **claim 22**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein mapping the portions comprises mapping the refinement portion into a constellation having a discrete number of possible values (Schreiber: digital, Level 2 Digital, Fig.8). Examiner maintains that the refinement portion can be transmitted either by Level 2 digital only or by Level 2 Analog only in Schreiber (Fig.8) without level 3.

Regarding **claim 24**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near-lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein representing the difference between the coarse portion and the video image by a refinement portion formed of a plurality of refinement sub-portions, each of which has a

Art Unit: 2482

smaller side to side constellation size (Schreiber: Fig.7). Examiner interprets the side to side distance as angular (circumferential) distance between the digital signals.

Therefore the refinement portion (analog signal in Schreiber) does not have this component (zero distance), but has a perpendicular (radial) component.

Regarding **claim 25**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near –lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein the coarse and refinement portions (Layered coding with Near-lossless encoding with coarse portion) together represent the video image in a non-compressed standard (Not a compression standard such as MPEG) representation of color video with at most slight filtering (No filtering).

Regarding **claim 27**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near –lossless compression based on a bounded difference from the provided image, as applied to claim 12, discloses wherein compressing the video image comprises compressing such that the difference between the coarse portion and the provided image is bounded (Seroussi: Uniform bound E (e.g. 1, 2, 5, 7) on the difference between each original pixel and its decoded pixel, col.25, line 40-43) for substantially all the pixels of the image (all the pixels in image).

Regarding **claim 31**, Schreiber discloses everything claimed above (see claim 26). However, Schreiber fails to disclose wherein representing the difference by a refinement portion comprises determining for each pixel a difference between the

Art Unit: 2482

coarse portion and the provided image and wherein each value of the refinement portion is related to at most 100 pixels of the image.

Seroussi specifically discloses a near lossless compression using prediction based on already encoded 6 neighboring pixels (Fig.3), in order to provide low complexity compression (col.6, line 54-56).

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber by substituting the source coding based on MPEG (Schreiber: Fig.6) for the level 1 (coarse portion) with near lossless compression using prediction based on already encoded 6 neighboring pixels, as taught by Van, in order to provide low complexity compression. The Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near lossless compression using prediction based on already encoded 6 neighboring pixels, has all the features of claim 31.

Regarding **claim 32**, Schreiber discloses everything claimed above (see claim 26). However, Schreiber fails to disclose wherein representing the difference by a refinement portion comprises determining for each pixel a difference between the coarse portion and the provided image and wherein each value of the refinement portion is related to at most 10 pixels of the image.

Seroussi specifically discloses a near lossless compression using prediction based on already encoded 6 neighboring pixels (Fig.3), in order to provide low complexity compression.

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber by substituting the source coding based on MPEG (Fig.6) for the level 1 (coarse portion) with near lossless compression using prediction based on already encoded 6 neighboring pixels, as taught by Van, in order to provide low complexity compression. The Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near lossless compression using prediction based on already encoded 6 neighboring pixels, has all the features of claim 12.

Regarding **claim 35**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near lossless compression using prediction based on already encoded 6 neighboring pixels, as applied to claim 31 and 33, discloses wherein at least one value of the refinement portion represents a difference between the coarse portion and the provided image at a point on the image interpolated for two or more neighboring pixels (Seroussi: Fig.3 shows prediction based on interpolation of 6 neighboring pixels).

Regarding **claim 38**, the Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near lossless compression using prediction based on already encoded 6 neighboring pixels, as applied to claim 31 and 33, discloses wherein the refinement portion is mapped without undergoing a transform into a non-image domain (there is no transformation to other domain in near lossless compression).

Art Unit: 2482

12. **Claims 23** are rejected under 35 U.S.C. 103(a) as being unpatentable over Schreiber in view of Seroussi, further in view of Shattil (US 2004/0,141,548), hereafter referenced as Shattil.

Regarding **claim 23**, Schreiber and Seroussi disclose everything claimed above (see claim 12). However, they fail to disclose wherein transmitting the mapped symbols comprise transmitting over a multi-input multi-output MIMO link.

In the analogous field of endeavor, Shattil discloses Software Adaptable High Performance Multicarrier Transmission. Shattil specifically discloses wherein transmitting the mapped symbols comprise transmitting over a multi-input multi-output MIMO link (MIMO, paragraph 233), for the purpose of PAPR-reduction (paragraph 133).

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber and Seroussi by specifically providing transmitting the mapped symbols over a multi-input multi-output MIMO link, for the purpose of PAPR-reduction. The Schreiber Multiresolution source and channel coding, substituting source encoder with the Seroussi near -lossless compression based on a bounded difference from the provided image, further incorporating the Shattil transmitting the mapped symbols over a multi-input multi-output MIMO link, has all the features of claim 23.

13. **Claim 30** is rejected under 35 U.S.C. 103(a) as being unpatentable over Schreiber in view of Shattil.

Regarding **claim 30**, Schreiber discloses everything claimed above (see claim 26). However, Schreiber fails to disclose wherein transmitting the mapped symbols comprise transmitting over a multi-input multi-output MIMO link.

Shattil specifically discloses wherein transmitting the mapped symbols comprise transmitting over a multi-input multi-output MIMO link (MIMO, paragraph 233), for the purpose of PAPR-reduction (paragraph 133).

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber by specifically providing transmitting the mapped symbols over a multi-input multi-output MIMO link, for the purpose of PAPR-reduction. The Schreiber Multiresolution source and channel coding, incorporating the Shattil transmitting the mapped symbols over a multi-input multi-output MIMO link, has all the features of claim 30.

14. **Claim 41** is rejected under 35 U.S.C. 103(a) as being unpatentable over Schreiber.

Regarding **claim 41**, Schreiber discloses everything claimed above (see claim 26). In addition, Schreiber teaches wherein mapping the portions comprises mapping the refinement portion into a constellation such that its value degrades gracefully with noise (analog transmission of refinement portion (level 2 analog) in Fig.8, because it was well known that analog transmission degrades gracefully with noise compared to digital transmission which has a cliff effect).

Art Unit: 2482

15. **Claims 42-44, 46, and 49** are rejected under 35 U.S.C. 103(a) as being unpatentable over Schreiber in view of Taubman (US 6,778,709), hereafter referenced as Taubman.

Regarding **claim 42**, Schreiber discloses A method of transmitting video images, comprising:

providing a video image (Video In, Fig.1) ;

compressing the video image into a coarse portion (coder 1, Fig.1), having a first average number of bits per pixel (bits per pixel is calculated from bit rates of video compression and frames/sec and pixels in frame);

representing the difference (subtracted from original video, Fig.1) between the coarse portion and the video image by a refinement portion (output of coder 2, Fig.1);

mapping the coarse and refinement portions into symbols of a constellation (Fig.7 Constellation) in value form,

such that spatial proximity between two symbols, each of which two symbols is associated with a different respective refinement value (Fig.7 shows the hybrid constellation - 64 PSK digital signal (coarse symbol) which should be dots in the constellation with 64 angular directions without line segments, and the analog signal is represented by the length of lines at each digital signal constellation), is related to a numeric proximity (Refinement portion is representation of the residual - subtraction of coarse signal from the original signal as shown in Fig.1) between the respective refinement values;_and

transmitting the mapped symbols to a receiver (Transmitter at Fig.8).

Art Unit: 2482

However Schreiber fails to disclose having an average equivalent bit rate of the refinement portion requiring a greater number of bits per pixel, for representation, than the first average number.

In the analogous field of endeavor, Taubman discloses Embedded Block Coding With Optimized Truncation. Taubman specifically discloses having an average equivalent bit rate of the refinement portion requiring a greater number of bits per pixel, for representation, than the first average number (0.25 bits per pixel for the first layer, 0.5 bits per pixel for the second layer, col.14, line 14-18), in order to provide efficient bit rate control (col.2, line 12-13).

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber by specifically providing higher average bit rate for the enhanced layer compared to the bitrate of coarse layer, as taught by Taubman, in order to provide efficient bit rate control. The Schreiber Multiresolution source and channel coding, incorporating the Taubman higher average bit rate for the enhanced layer compared to the bitrate of coarse layer, has all the features of claim 42.

Regarding **claim 43**, Schreiber and Taubman disclose everything claimed above (see claim 42). Schreiber further discloses wherein the refinement portion is not represented by bits (Level 2 Analog, Fig.8).

Regarding **claim 44**, Schreiber and Taubman disclose everything claimed above (see claim 42). Schreiber further discloses wherein the refinement portion has a

Art Unit: 2482

predetermined number of values for each symbol. (Level 2 Digital Fig.8, without analog portion).

Regarding **claim 46**, Schreiber and Taubman disclose everything claimed above (see claim 42). Schreiber further discloses wherein mapping the portions comprises mapping the coarse and refinement portions separately into symbols and superimposing the symbols onto each other (Fig.7).

Regarding **claim 49**, the Schreiber Multiresolution source and channel coding, incorporating the Taubman higher average bit rate for the enhanced layer compared to the bitrate of coarse layer, as applied to claim 42, discloses wherein the average equivalent bit rate of the refinement portion requires for representation at least twice the number of bits from the first average number (Taubman: 0.25 bits per pixel for the first layer, 0.5 bits per pixel for the second layer, col.14, line 14-18).

16. **Claims 45 and 47-48** are rejected under 35 U.S.C. 103(a) as being unpatentable over Schreiber in view of Taubman, further in view of Seroussi.

Regarding **claim 45**, Schreiber and Taubman disclose everything claimed above (see claim 42). Schreiber and Taubman fail to disclose wherein compressing the video image comprises compressing such that the difference between the coarse portion and the provided image is bounded to have at most ten different possible values.

Seroussi specifically discloses near-lossless encoder compressing the video image comprises compressing such that the difference between the coarse portion and the provided image is bounded to have at most ten different possible values. (Uniform

Art Unit: 2482

bound E (e.g. 1, 2, 5, 7) on the difference between each original pixel and its decoded pixel, col.25, line 40-43), in order to provide low complexity compression (col.6, line 54-56).

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber by substituting source encoder with the Seroussi near-lossless encoder, as taught by Seroussi, in order to provide low complexity compression. The Schreiber Multiresolution source and channel coding, incorporating the Taubman higher average bit rate for the enhanced layer compared to the bitrate of coarse layer, further substituting source encoder with the Seroussi near-lossless encoder, has all the features of claim 45.

Regarding **claim 47**, the Schreiber Multiresolution source and channel coding, incorporating the Taubman higher average bit rate for the enhanced layer compared to the bitrate of coarse layer, further substituting source encoder with the Seroussi near-lossless encoder, as applied to claim 45, discloses wherein representing the difference by a refinement portion comprises determining for each pixel a difference between the coarse portion and the provided image and wherein each value of the refinement portion is related to at most 10 pixels of the image (Seroussi: Fig.3 shows the prediction based on 6 neighboring pixels).

Regarding **claim 48**, the Schreiber Multiresolution source and channel coding, incorporating the Taubman higher average bit rate for the enhanced layer compared to the bitrate of coarse layer, further substituting source encoder with the Seroussi near-lossless encoder, as applied to claim 45, discloses wherein the coarse portion is

Art Unit: 2482

protected by a forward error correction code (Schreiber: FEC, Fig.8), while the refinement portion (Schreiber: Level 2 Analog, Fig.8) is transmitted without protection by a forward error correction code.

17. **Claims 50-54** are rejected under 35 U.S.C. 103(a) as being unpatentable over Schreiber in view of Van (US 2003/0,179,938).

Regarding **claim 50**, Schreiber discloses A method of transmitting video images, comprising:

providing a video image (Video In, Fig.1);

compressing the video image into a coarse portion (coder 1, Fig.1), using a near lossless compression;

method achieving less than a 15:1 compression ratio;

representing the difference (subtracted from original video, Fig.1) between the coarse portion and the video image by a refinement portion (output of coder 2, Fig.1) in value form;

mapping the coarse and refinement portions into symbols of a constellation (Fig.7 Constellation),

such that spatial proximity between two symbols, each of which two symbols is associated with a different respective refinement value (Fig.7 shows the hybrid constellation - 64 PSK digital signal (coarse symbol) which should be dots in the constellation with 64 angular directions without line segments, and the analog signal is represented by the length of lines at each digital signal constellation), is related to a

Art Unit: 2482

numeric proximity (Refinement portion is representation of the residual - subtraction of coarse signal from the original signal as shown in Fig.1) between the respective refinement values;_and transmitting the mapped symbols to a receiver (Transmitter at Fig.8).

However, Schreiber fails to disclose using a near lossless compression for coarse portion and method achieving less than a 15:1 compression ratio.

In the analogous field of endeavor, Van discloses Device and Method for Compressing a Signal. Van specifically discloses near lossless compression based on a desirable compression ratio (paragraph 6 and 7), in order to combat a limited bandwidth (paragraph 6). The compression ratio is dictated by a limited bandwidth, which could be less than 15:1.

Therefore, given this teaching, it would have been obvious to one of ordinary skill in the art at the time invention was made to modify Schreiber by substituting the source coding based on MPEG (Fig.6) for the level 1 (coarse portion) with near lossless compression based on desirable compression ratio of less than 15:1, as taught by Van, in order to combat a limited bandwidth. The Schreiber Multiresolution source and channel coding, substituting source encoder with the Van near lossless compression based on desirable compression ratio of less than 15:1, has all the features of claim 50.

Regarding **claim 51**, Schreiber and Van disclose everything claimed above (see claim 50). Schreiber further discloses wherein mapping the portions comprises mapping the coarse and refinement portions separately into symbols and superimposing the symbols onto each other (Fig.7).

Regarding **claim 52**, Schreiber and Van disclose everything claimed above (see claim 51). Schreiber further discloses wherein the coarse portion is protected by a forward error correction code (Schreiber: FEC, Fig.8), while the refinement portion (Schreiber: Level 2 Analog, Fig.8) is transmitted without protection by a forward error correction code.

Regarding **claim 53**, Schreiber and Van disclose everything claimed above (see claim 50). Van teaches wherein compressing the video image comprises compressing with a compression ratio of less than 8:1 (Van: a desirable compression ratio, paragraph 6, could be 8:1 because of limited bandwidth).

Regarding **claim 54**, Schreiber and Van disclose everything claimed above (see claim 50). Van teaches wherein compressing the video image comprises compressing with a compression ratio of less than 12:1 (Van: a desirable compression ratio, paragraph 6, could be 12:1 because of limited bandwidth).

Conclusion

18. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the

Art Unit: 2482

shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

19. Any inquiry concerning this communication or earlier communications from the examiner should be directed to HEE-YONG KIM whose telephone number is (571)270-3669. The examiner can normally be reached on Monday-Thursday, 8:00am-5pm EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Marsha Banks-Harold can be reached on 571-272-7905. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/HEE-YONG KIM/
Examiner, Art Unit 2482

/Andy S. Rao/

Application/Control Number: 10/574,023

Page 25

Art Unit: 2482

Primary Examiner, Art Unit 2486

February 24, 2011